



Resin Paint Primer DPM (Damp proof membrane) REF :RPDPM2025/01

DESCRIPTION

Resin Paint Primer DPM is a two-component epoxy resin surface applied membrane that is tolerant of residual moisture in concrete floors. This enables earlier access onto new concrete substrates for the application of screeds, coatings and other floor coverings including carpets, tiles, vinyl and wood.

Resin Paint Primer DPM is also used for existing concrete slabs where there is no damp proof membrane or where a degree of moisture tolerance is required for a resin floor system being installed.

ADVANTAGES

- Easy application
- Application onto substrates with hygrometer readings up to 97%
- Solvent free
- Low odour
- Excellent adhesion

RECOMMENDED USES

- Concretes with no dpm
- Where a dpm is ineffective
- Polymer screeds
- Cementitious underlayments

PRODUCT INFORMATION

System thickness (dry)	Solids content by weight	Pack sizes	Pack make up	Shelf life	Storage
250 microns	100%	5 kg. & 15 kg.	1 x Base 1 x Hardener	12 Months (Base & Hardener)	Keep out of direct sunlight. Store in a dry place, not below 15°C

DRYING TIMES & COVERAGE RATES at 20°C

Coverage rate	Pot life	Recoat time	Light traffic	Full traffic	Full chemical cure
5 Kg. will cover 20 sq m @ 200 microns thickness	30 Minutes from mixing	8 hours or once surface has lost tackiness	24 Hours	72 Hours	Up to 7 Days

